

## PT „PARTIAL TRANSFER” – SECURITY LABEL



- ❖ This is a high tack security label. When lifted it leaves an „OPEN VOID” security message on the application surface. Therefore tampering can be traced at a glance.
- ❖ With the high tack characteristic it is useful for almost all kind of applications: porous or non-porous even fibrous surfaces.
- ❖ These labels are heat and freeze resistant up to a certain level and thus cannot be tampered with.
- ❖ Unlike other “VOID” tamper evident materials this has a further benefit in that the residue which is left after removal can be easily and quickly rubbed away.
- ❖ Partial Transfer labels can be customized by placing personalized markings, company logo or optional barcode on the labels.



### APPLICATION

- ❖ This type is mostly used for the sealing of bags, boxes and such equipment where the residue left on the surface after removal does not cause any problem. It is recommended for cards of fibrous surfaces however it is not really effective on normal writing paper.
- ❖ Clean the surface before using the label!
- ❖ Recommended working temperature: 10-35 °C. The adhesive reaches the full efficiency in 10 minutes. Store in dry conditions, between 10-20°C (50-68°F), kept in box, out of direct sunlight.
- ❖ Not recommended on rough surfaces.
- ❖ Test the label on the surface before use.

Seal type	Dimensions (mm)	Material	Stock version	Further marking facilities
PT	Standard		√	√
Partial transfer security label	30 mm x 20 mm 58 mm x 20 mm 90 mm x 30 mm 110 mm x 30 mm	OPP foil with special adhesive	Orange, Sequential numbered	Logo, barcode and any special serial number available

All statements, technical information and recommendations herein are based on tests the Manufacturer believes to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller or Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.