

TAMPER EVIDENT BLUE SECURITY TAPE – S-TYPE with perforation and sequential numbering



- 1 The tamper evident security tape is a convenient and secure way to prove the closed state of goods. Opening attempts or any tampering during shipping or storage will not remain without a trace.
- 2 When tearing up the tamper evident security tape it will leave an unalterable trace both on the operating surface and the tape's surface.
- 3 Designed to be especially efficient on cardboard boxes, impregnated, or laminated surfaces.
- 4 Shipped in rolls with perforation and sequential numbering.
- 5 Freezing temperature: -40°C
Holding power at +60°C >24 hrs



SPECIFICATION

Tamper evident security tape. When peeled off its lower layer remains on the surface of application and „VOID OPENED” hidden message appears. This „VOID OPENED” text becomes visible on the surface of the tape as well. Reinstating the tape without trace is not possible.

APPLICATION

- Application should be done with great care. Apply the tamper evident security tape by pressing down either using a handheld tape dispenser or by hand. (In the latter case it may be necessary to repeatedly smooth down the edges of the tape.) If the tape is rolled down too fast, the void message may appear because of the tape's sensitivity.
- Recommended application temperature: between +15°C to +25°C.
- The quality of the void message depends on the quality of the application surface. In the interest of proper usage testing the security tape is a must before applying it on the application surface in the application circumstances.

RECOMMENDED STORAGE

Between +10°C and +20°C, and away from direct sunlight, in a closed box.

Type: S	Dimensions (mm)	Material	Stock version	Customisation
- Tamper evident security tape for cardboard boxes, designed especially for the packaging industry.	48 mm x 50 m/roll With perforation in every 150 mm With sequential numbering	PET foil with acrylic adhesive	Colour: Blue, Void message: „VOID OPENED” Text on tape's surface: „SECURITY SEAL”	Standard stock version only. Further customisation of the stock version is not possible.

All statements, technical information and recommendations herein are based on tests the Manufacturer believes to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller or Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer

HITEC KFT. • Address: H-1119 BUDAPEST, FEHÉRVÁRI ÚT 81., HUNGARY

Tel: +36 1 205-5838 • marketing@hitec.hu • www.hitec.hu • Fax: +36 1 205-5815