

TAMPER EVIDENT SECURITY TAPE – TT



- 1 The security tape is the most convenient solution for packaging purposes if the content of box has to be secured and any attempt of tampering has to be traced easily.
- 2 When the tape is lifted the security message and substrate remains firmly on the application surface.
- 3 The security tape is mainly applied on cardboard boxes and it is effective either on normal, laminated or impregnated cardboard.
- 4 The seal is supplied in rolls and it is very easy to handle. Our stock version is perforated at every 152.4 mm
- 5 For orders above 200 rolls the tapes can be customized with personal face printing, security message, sequential numbering or company logo as an option. Not perforated tape is possible, as well in case of agreement.



SPECIFICATION

The security tape is tamper evident: if it is lifted, the “VOID OPENED” security message remains firmly on the application surface and the text can be traced on the top layer of the seal as well.

APPLICATION

- ❖ Apply the tape to the box using pressure (via hand tape dispenser) or by rubbing your hand over the tape. The tape should be applied with great care, if the tape is unwound too fast, pre- voiding may occur.
- ❖ Recommended application temperature +15°C to +25°C.
- ❖ Quality of voiding is dependent upon the quality of the application surface. The customer should always test the tape on the application surface and in the application environment to confirm suitability..

RECOMMENDED STORAGE

Between +10°C and +20°C, and away from direct sunlight, in a closed box.

Type: TT	Dimensions (mm)	Material	Stock version	Customisation
- Tamper evident security tape for cardboard boxes, designed especially for the packaging industry.	50,8 mm x 66 m /roll perforation at every 152,4 mm sequential numbering	BOPP foil with acrylic adhesive	Colour: red, with white window Void message: „VOID OPENED” Text on tape’s surface: „SECURITY SEAL” in red with sequential numbering	Further customisation is available.

All statements, technical information and recommendations herein are based on tests the Manufacturer believes to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller’s and Manufacturer’s only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for it’s intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller or Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.