



Conditions of use, storage and transport for packages and bags with security tape

These products are intended for the storage and transport of money and other valuables. This type of packaging has full protection against third party interference.

Closure of the package wherein a safe tape is used:

Closing the package using security tape should be carried out at room temperature (between 18°C & 23°C). Removal of the aperture should be smooth (without jerking), then you should approach security tape with adhesive to the opposite edge of the opening line and strongly squeeze with your fingers along the entire length of the security tape. For subcooled envelopes, wait to stabilize the temperature. Any attempt to open results in permanent marks visible on the place where the sealing tape was applied.

Security tape adhesive reaches full strength within 10 minutes after sealing.

Storage and transport:

The packages should be stored and transported at a temperature between 10°C and 30°C and relative humidity not exceeding 80%. Long hours of exposure to temperatures between 40°C and 45°C can cause the activation of thermo printing resulting in a permanent color change of the protection. Packaging must not be stored near heat sources. Pallet units with finished product should be stored in roofed areas to prevent effects of direct sunlight, atmospheric factors, moisture.

When transporting or storing the packaging at a temperature below 10 ° C, it is recommended that the package should be put in room temperature (between 18°C & 23°C) for 24 hours to stabilize the temperature. The product should be transported in covered means of transport, in accordance with the transport regulations. Loading units should be clean and secured against displacement, dirt, moisture and damage.

Compliance with these conditions guarantees the maintenance of physical and mechanical properties of packaging.